LAMOSA®

Edition: 2025

SPEC SHEET

TYPE: PORCELAIN TILE (GL) PRODUCT: **OSLO US** COLOR: **GREY** SIZE: **30 x 60 cm (12 x 24 in)**

TECHNICAL FEATURES				SPECIFICATION		TEST
				mm	in	
1. Dimensions	1.1	Length		599.8 ± 0.5% or Max. ± 2.0	23.6 ± 0.5% or Max. ± 0.08	ASTM C499
	1.2	Width		300.0 ± 0.5% or Max. ± 2.0	11.8 ± 0.5% or Max. ± 0.08	ASTM C499
	1.3	Wedging	1.3.1 Length	599.8 ± 0.5% or Max. ± 2.0	23.6 ± 0.5% or Max. ± 0.08	ASTM C502
			1.3.2 Width	300.0 ± 0.5% or Max. ± 2.0	11.8 ± 0.5% or Max. ± 0.08	ASTM C502
	1.4	Surface flatness	1.4.1 Warpage Diagonal	670.6 ± 0.5% or Max. ± 1.8	26.4 ± 0.5% or Max. ± 0.07	ASTM C485
			1.4.2 Warpage Edge	599.8 ± 0.5% or Max. ± 1.8	23.6 ± 0.5% or Max. ± 0.07	ASTM C485

TECHNICAL FEATURES			UNITS	SPECIFICATION	TEST
2. Physical properties	2.1	Water absorption	%	≤ 0.5	ASTM C373
	2.2	Breaking strength	lbf	≥ 275	ASTM C648
	2.3	Visible abrasion resistance	-	IV	ASTM C1027
	2.4	Thermal shock resistance	-	Resist	ASTM C484
	2.5	Crazing resistance	-	Resist	ASTM C424
	2.6	Resistance to freeze	-	Resist	ASTM C1026
	2.7	Dynamic coefficient of friction (DCOF)	-	≥ 0.42	ANSI A326.3
3. Chemical properties	3.1	Chemical resistance	-	Class A (Resist)[1]	ASTM C650
	3.2	Stain resistance	-	Class A	ASTM C1378
4. Shade	V0 V1  V2 V3 V4				

Product Oslo US Grey 30 x 60 cm (12 x 24 in) meets all the technical specifications established in the ANSI A137-1 Standard.

[1]Avoid contact of the ceramic material with chemicals such as Muriatic Acid, Hydrofluoric Acid, Chlorine, Gasoline, Thinner, Diesel, cleaners that contain Potassium Hydroxide and other similar products, since the use of such substances can cause severe changes in the tile surface, altering its original appearance.

Issued by:

JOVANNI ARANA ROJAS
SPECS AND QUALITY STANDARDS

Grupo Lamosa - Información de uso público